

Concrete Admixtures, Adhesives & Aids

EDECON SUNOUT-C

DESCRIPTION

Edecon SunOut-C is a concentrated, polymer-emulsion curing compound for concrete. **Edecon SunOut-C** forms a film when applied to fresh concrete, diminishing the rate of hydration. It allows the concrete to retain its mixing water so that it may complete its principal function of completely hydrating the cement particles.

Specification: ASTM C-309, Type 1 or 1-D, Class A

USES

Edecon SunOut-C is ideal for interior and exterior concrete surfaces including:

- Floors
- Ramps
- Platforms
- Pavements
- ...and many others

ADVANTAGES

- Provides a positive cure for fresh concrete
- Leaves no damaging residues
- Non-staining; ideal for exposed surfaces
- Pigmented for ease of placement

TECHNICAL INFORMATION

Edecon SunOut-C offers the following functions depending upon the condition of the concrete:

On fresh concrete:

Edecon SunOut-C reduces evaporation and plastic shrinkage.

On recently placed and cured concrete:

Edecon SunOut-C provides a protective, hard mineral membrane.

On hardened concrete:

Edecon SunOut-C is used to provide a hard, new working surface.

On vertical concrete:

Edecon SunOut-C strengthens and improves the surfaces' resistance to inclement environments when applied immediately after removing forms.

PHYSICAL CHARACTERISTICS

pH	6.9
Specific Gravity	1.25
Weight per Gallon	10.432 lbs
Weight per Liter	1.25 kg
Appearance	Opaque white
H₂O Solubility	100% soluble
Odor	Acrid

APPLICATION

Apply diluted **Edecon SunOut-C** with a sprayer to create a continuous and uniform coat over the surface.

DOSAGE

Edecon SunOut-C is a highly concentrated product, which can be diluted with up to six (6) parts water.

PACKAGING

All of our products are available in the following delivery container sizes:

- Sample Jug – 19 liter / ≈ 5 US gallon
- Sample Mini-drum – 57 liter / ≈ 15 gallon
- Drum/Barrel – 200 liter / ≈ 53 gallon volume in a 55 US gallon drum
- Transport Tote – 1,000 liter / ≈ 263 US gallon
- Various Sized Tankers – available for bulk volumes

WARRANTY: The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages

www.edecon.net

