

Concrete Admixtures, Adhesives & Aids

EDECON TR-34

DESCRIPTION

Edecon TR-34 is a concrete release agent, which allows forms to be stripped cleanly, evenly and without voids through chemical reaction, rather than lubrication. **Edecon TR-34** contains chemicals that combine with natural concrete alkali eliminating "drag" between the poured concrete and the form. This eases the removal of forms, eliminating form cleaning and resulting in a smooth, high white finish.

Edecon TR-34 is fully compatible with pre-oiled plywood, and will not wash off at pour time. It prevents bleed water from penetrating the wood, thereby eliminating rot and raised or warped grain. Successive use of **Edecon TR-34** makes the wood more impermeable, allowing for multiple uses of the same form.

Specification: ACI-309

USES

Edecon TR-34 is excellent for use on steel, patent and fiber tube forms. It reacts chemically with steel and forms a rustproof film as well as a positive release. **Edecon TR-34** is most effective when applied to fiber tubes, even those coated with wax or plastic. It allows tubes to be stripped in under ten (10) days, where required, and aids hand rubbing.

ADVANTAGES

Edecon TR-34 is particularly beneficial when sprayed daily on machine mixers, hoist buckets, wheelbarrows, power trowels, spreaders, face mixers and other equipment. It not only protects against rust but also keeps concrete or plaster "build-up" soft for easy clean up.

TECHNICAL INFORMATION

Edecon TR-34 is used as a stripping or demolding agent (form remover) for all wetcast concrete application.

PHYSICAL CHARACTERISTICS

pH	6.5
Specific Gravity	0.86
Weight per Gallon	7.177 lbs
Weight per Liter	0.86 kg
Appearance	Blue/green
H ₂ O Solubility	Non-soluble
Odor	Hydrocarbon

APPLICATION

Edecon TR-34 is applied at the rate of approximately 400 to 600 square feet per US gallon (11 to 15 square meters per liter) on wood and 600 to 800 square feet per US gallon (14 to 19 square meters per liter) on metal.

Edecon TR-34 is applied using a sprayer. Due to the much greater coverage and ease of application, **Edecon TR-34** is as inexpensive as ordinary form oil.

Edecon TR-34 is safe to handle, and will not endanger health when applied according to manufacturer's specifications.

DOSAGE

Edecon TR-34 comes ready for use, no mixing is necessary. Spray in a fine mist as required.

For industrial use only
SHAKE WELL BEFORE USE.
WARNING: FLAMMABLE LIQUID

PACKAGING

All of our products are available in the following delivery container sizes:

- Sample Jug – 19 liter / ≈ 5 US gallon
- Sample Mini-drum – 57 liter / ≈ 15 gallon
- Drum/Barrel – 200 liter / ≈ 53 gallon volume in a 55 US gallon drum
- Transport Tote – 1,000 liter / ≈ 263 US gallon
- Various Sized Tankers – available for bulk volumes

WARRANTY: The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages

www.edecon.net

