

Concrete Admixtures, Adhesives & Aids

EDECON EPOSEAL

DESCRIPTION

Edecon Eposeal is a one-component synthetic resin compound sealer designed for use on concrete, brick, metal or wood surfaces. Once applied, it provides a glossy finish resistant to chemicals, abrasion, oil and grease.

Specification:

USES

- To seal concrete and brick walls and floors
- To protect concrete exposed to weathering conditions
- To seal concrete roofs and decks

ADVANTAGES

- Fast air dry
- Good hardness
- Enhances colors of brick walls and floors
- Glossy, transparent finish
- Protects concrete and brick surfaces from dusting
- Only one coat necessary in most applications
- The advantage is in the penetrant

TECHNICAL INFORMATION

PHYSICAL CHARACTERISTICS

	pH	
	Specific Gravity	
	Weight per Gallon	
	Weight per Liter	
	Appearance	
	H ₂ O Solubility	
	Odor	

APPLICATION

Surfaces to be treated must be sound; holes, fissures and spalled areas must be filled or patched. Dust, dirt, oil, wax, mildew, rust and other foreign material must be removed. If the surface is questionable, apply **Edecon Eposeal** to a test area to be sure of adequate bonding and hardness.

Apply **Edecon Eposeal** to form a continuous, uniform film by spraying, use a soft bristle push broom, shorthaired paint roller or rubber squeegee.

Edecon Eposeal should be applied in a well-ventilated area. Gloves and protective eyewear are recommended, especially for those sensitive to solvents. The temperature of the surface to be treated must not be less than 40°F.

Coverage:

Rough Surface: 100 to 200 ft² per gallon (9.3 to 18.6 m² per 3.8 l)

Smooth Surface: 200 to 350 ft² per gallon (18.6 to 32.5 m² per 3.8 l)

DOSAGE

PACKAGING

All of our products are available in the following delivery container sizes:

- Sample Jug – 19 liter / ≈ 5 US gallon
- Sample Mini-drum – 57 liter / ≈ 15 gallon
- Drum/Barrel – 200 liter / ≈ 53 gallon volume in a 55 US gallon drum
- Transport Tote – 1,000 liter / ≈ 263 US gallon
- Various Sized Tankers – available for bulk volumes

WARRANTY: The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages

www.edecon.net

