

Concrete Admixtures, Adhesives & Aids

EDECON ROOFCEM

DESCRIPTION

Edecon Roofcem is a two-part cementitious compound where the dry material is mixed with a liquid polymer, producing a membrane that breathes and which adheres strongly becoming an integral part of the concrete surface.

Specificaiton:

USES

- Seals and protects concrete roofs and walls exposed to high humidity.
- To paint new concrete soffits.

ADVANTAGES

- The membrane breathes, eliminating the formation of water droplets from condensation.
- Strong adherence to the concrete surface.
- White color helps keep interiors cool.
- Membrane can be coated or painted with other materials.
- Penetrates and seals small pores, adding strength to the concrete mass.
- Easy to apply.
- Economical.

TECHNICAL INFORMATION

PHYSICAL CHARACTERISTICS

	pH	
	Specific Gravity	
	Weight per Gallon	
	Weight per Liter	
	Appearance	
	H ₂ O Solubility	
	Odor	

APPLICATION

Surface Preparation: The surface should be clean, completely dry and free of dust, grease, etc. Remove any tar and rubber or aluminum membranes.

1. Dilute **Edecon Bodax-601** at a ratio of 1:1 with water and combine with the powder component in its bag. Mix and squeeze until a thick, even paint-like consistency is achieved. Mix only one gallon at a time as **Edecon Roofcem** dries very quickly.
2. Apply two (2) coats of **Edecon Roofcem**, making sure to paint over all visible fissures and allowing two (2) hours drying time between coats. Apply to the entire surface including any beams and parapets.

DOSAGE

PACKAGING

All of our products are available in the following delivery container sizes:

- Sample Jug – 19 liter / ≈ 5 US gallon
- Sample Mini-drum – 57 liter / ≈ 15 gallon
- Drum/Barrel – 200 liter / ≈ 53 gallon volume in a 55 US gallon drum
- Transport Tote – 1,000 liter / ≈ 263 US gallon
- Various Sized Tankers – available for bulk volumes

WARRANTY: The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages

www.edecon.net

