

Concrete Admixtures, Adhesives & Aids

EDECON TRANSEAL

DESCRIPTION

Edecon TranSeal is a one-part, silicone-based, clear liquid penetrating sealer. **Edecon TranSeal** is specially formulated for concrete or other porous surfaces exposed to moisture from rain, groundwater, etc.

Specification:

USES

- As an integral water-repellent
- Ideal for use with a variety of surfaces: brick, stone, marble, concrete and more
- As a protective treatment for bridges, retaining walls, beams and columns
- For pre-fabricated lightweight concrete panels
- Inhibits corrosion in concrete due to water penetration

ADVANTAGES

- Eliminates water infiltration of vertical or horizontal surfaces
- Protects facades from dust and soot
- Transparent on treated surface
- Extends the working life of all types of surfaces

TECHNICAL INFORMATION

PHYSICAL CHARACTERISTICS

pH	
Specific Gravity	
Weight per Gallon	
Weight per Liter	
Appearance	Colorless
H ₂ O Solubility	
Odor	

APPLICATION

Surface Preparation: Surfaces should be clean, dry and free of dust, tar, oil, paint or other extraneous material. Cracks or fissures should be repaired at least three (3) days prior to application.

Application: **Edecon TranSeal** is applied using roller, brush or sprayer. Apply two (2) coats, saturating the entire surface. Allow the first coat to dry completely before applying the second. Drying time is approximately one (1) hour at 75°F (24°C).

Coverage: Depending on surface porosity, first coat coverage could be as little as 200 square yards per US gallon (5 square meters per liter). Subsequent coats should extend coverage to as much as 1000 square yards per US gallon (25 square meters per liter).

Do Not Apply In Direct Sunlight
Protect From Rain For At Least 3 Hours After Placement

FLAMABLE

Avoid Open Flame or Spark
-NO SMOKING-

DOSAGE

PACKAGING

All of our products are available in the following delivery container sizes:

- Sample Jug – 19 liter / ≈ 5 US gallon
- Sample Mini-drum – 57 liter / ≈ 15 gallon
- Drum/Barrel – 200 liter / ≈ 53 gallon volume in a 55 US gallon drum
- Transport Tote – 1,000 liter / ≈ 263 US gallon
- Various Sized Tankers – available for bulk volumes

WARRANTY: The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages

www.edecon.net

